

Datasheet

DGLPFNWLC26, DGLPWLC26 - Multi-Tech Proximity Reader

Product Description

The DGLPFNWLC26 is a mullion style reader with Wiegand output, and the DGLPWLC26 is a proximity reader with Wiegand output.

These readers are for connection to access control systems such as ATRIUM. The polycarbonate design make it a durable solution for multiple applications, whether indoors or outdoors.

DGLPFNWLC26



DGLPWLC26



Key Features

- Reads CDVI® and most popular 26-bit credential formats
- Indoor/outdoor application
- Dust and weather resistant
- DGLPFNWLC26: Sealed in epoxy
- Visual and audible feedback



Certification



DEEE



Certification



IP53



-22°F to 140°F
(-30°C to 60°C)

All the information contained within this document (pictures, drawings, features, dimensions, specifications), could be perceptibly different and can be changed without prior notice. Published: 22 August 2023. CDVI_DGLPFNWLC26_DGLPWLC26_DS_01_EN_LETTER_C

Product Specifications

Material:	Polycarbonate
Mounting:	Surface
Technology:	125 kHz
Security level:	Standard
Wiegand:	26, 30 or 44 bits
Read range:	DGLPFNWLC26: Up to 3.5" (8 cm) DGLPWLC26: Up to 4" (10 cm)
Weight:	DGLPFNWLC26: 4.1 oz, 118 g DGLPWLC26: 4 oz, 116 g

Electrical Specifications

Power input:	12 V DC
Consumption:	100 mA

Accessories



ISO25
Printable ISO Card



CS25
Clamshell Card



BTAG25
Blue Proximity Key Tag

